

FieldCast



Datasheet FieldCast Converter One Hybrid

- two channel converter: fiber to SDI / fiber to SDI
- data rate: 270Mb/s to 12Gb/s
- auto selection to input data rate
- compliant to all SD, HD, 2K, UltraHD and DCI 4K standards
- SDI video sampling: 4:2:2 and 4:4:4
- SDI color space: 4:2:2 and 4:4:4
- SDI audio sampling: 44kHz and 48kHz, 24bit
- two independent channels of fiber input, both with double SDI output
- fiber receive wavelength: 1290 nm to 1610 nm.
- fiber in sensitivity: 3G better than -20dBm, 12G better than -13dBm
- led indication: valid power input, valid power output, fiber input, data rate (3G, 6G or 12G)
- SDI connector: 4x 75ohm BNC connector for 2x SDI out and 2x SDI out
- fiber connector: hybrid ultra compact with 2Core single mode for 2x fiber in, two copper pins for DC+ and DC-, screw on type
- power input: 14-38VDC
- power input connector: hybrid fiber connector
- power output: 12VDC
- power output connector: cylindrical 5.5 mm., screw on type
- power output connector cable: cylindrical 5.5 mm. screw on type to XLR 4-pin female, 2 m.
- power consumption: < 3W
- stainless steel 14"-20 mounting plate

the fiber optic system

Hazepad 43, 1544 PW, Zaandijk, The Netherlands
+31 (0)75 6572290 | www.fieldcast.eu | info@fieldcast.eu