

# FieldCast



## Datasheet FieldCast Converter One

- two channel converter: fiber to SDI / fiber to SDI
- data rate: 270Mb/s to 12Gb/s
- auto selection to input data rate
- compliant to all SD, HD, 2K, UltraHD and DCI 4K standards
- SDI video sampling: 4:2:2 and 4:4:4
- SDI color space: 4:2:2 and 4:4:4
- SDI audio sampling: 44kHz and 48kHz, 24bit
- two independent channels of fiber input, both with double SDI output
- fiber receive wavelength: 1290 nm to 1610 nm.
- fiber in sensitivity: 3G better than -20dBm, 12G better than -13dBm
- led indication: valid power input, fiber input, data rate (3G, 6G or 12G)
- SDI connector: 4x 75ohm BNC connector for 2x SDI out and 2x SDI out
- fiber connector: compact 2Core single mode for fiber in, fiber out, screw on type
- power input: 12VDC nominal voltage
- power input connector: cylindrical 5.5 mm., screw on type
- power input connector cable: XLR 4-pin male to cylindrical 5.5 mm. screw on type, 2 m.
- power supply: 110-240VAc to 12VDC 10000mA with XLR 4-pin female connector
- power consumption: < 3W
- stainless steel 14"-20 mounting plate

the fiber optic system

Hazepad 43, 1544 PW, Zaandijk, The Netherlands  
+31 (0)75 6572290 | [www.fieldcast.eu](http://www.fieldcast.eu) | [info@fieldcast.eu](mailto:info@fieldcast.eu)